

SUVO Wax

Wax/oil based Anti-Rust product

Thin light brown wax/oil based Anti-Rust product with good penetration and moisture displacing properties, leaves a tough waxy layer.

Range of application:

SUVO Wax is particularly suitable for cavities, underbodies, joints, and similar areas. Especially effective on painted surfaces such as chassis frames and new body parts. Ideal for use over previously factory-applied wax coatings. Areas exposed to heavy wear should be finished with SUVO Belægning.

air-mix systems. To ensure proper penetration into joints and gaps, the temperature should not be below +15°C.

Package

01-502 / 25-lit can

01-501 / 60-lit drum

01-500 / 208-lit drum

Instructions for use:

Apply using low- or high-pressure systems. Before application, ensure the surface is dry and free from loose flakes and dirt. For cavity treatment, optimal results are achieved with

| Technical data | |
|--------------------------|---|
| Color: | Light brown |
| Consistency: | Liquid |
| Type of film: | Waxy |
| Density at 20° C: | 850 ± 30 kg/m ³ |
| Dry content: | 50 ± 2 % |
| Volatiles solvents: | <50 % |
| Film thickness: | 40 – 80 µm |
| Application temperature: | 15 – 25° C |
| Removal with: | Clairsolrens, Clearrens or LHG Rensevæske |
| Drying time: | 4 – 6 hours |
| Storing temperature: | 5 – 40° C |

For further information we recommend the safety data sheet or instruction on package.