

## SUVO Brun XL Industri

Oil/wax-based antirust product

SUVO Brown XL industry is a light brown oil/wax-based product with effective anti-rust inhibitor added. It has excellent corrosion protection and moisture displacement abilities. Leaves a tough wax layer.

---

**Range of application:**

Suitable for all types of steelwork requiring long-term corrosion protection. Also suitable as temporary transport protection when the product needs to be removed afterward.

**Package**

01-190 / 20-lit can  
01-191 / 60-lit drum

**Instructions for use:**

The items must be clean, dry and free of dirt. Do not apply below +8° C. The product must be stirred strongly or shaken then make more nice viscosity. Apply with brush or roller, a good quality which is suitable for oil products, or airless spray gun.

---

| Technical data           |   |
|--------------------------|---|
| Color:                   | Light brown                               |
| Consistency:             | Gel/wax                                   |
| Type of film:            | Medium/Hard wax                           |
| Density:                 | 200-250 mPas                              |
| Dry content:             | <50%                                      |
| Volatiles solvents:      | >40%                                      |
| Film thickness:          | 80 – 100 µm                               |
| Application temperature: | 15 – 35° C                                |
| Removal with:            | Clairsolrens, Clearrens or LHG Rensevæske |
| Drying time:             | 12 – 24 hours                             |
| Storing temperature:     | 5 – 25° C                                 |

**For further information we recommend the safety data sheet or instruction on package.**