

Rust Stop 80

Oil/wax-based anti-rust

Thin, light brown, penetrating, oil/wax-based anti-rust product with a high level of effective rust inhibitors, which means that Rust Stop 80 has an exceptional ability to protect against rust and stop incipient rust attacks. Rust Stop 80 has great penetration and moisture-penetrating properties, leaving a wax/greasy surface.

Range of application:

Rust Stop 80 is particularly suitable for cavities, bottom, plate assemblies and for finishing previously applied products. For protection of all types of metal surfaces that are to be protected against rust.

Instructions for use:

Apply with low- or high-pressure systems. Before application, the surface must be dry and free of loose flakes and dirt. When treating cavities, the best result is achieved with air mixing systems. To achieve the best

penetration into joints and slits, temp. should not be below +15° C.

Package

01-1055 / 500-ml spray (12 pcs / pack)
01-245 / 5-lit can
01-240 / 10-lit can
01-235 / 25-lit can
01-230 / 60-lit drum
01-225 / 208-lit drum
01-220 / 1000-lit tank

Technical data	
Color:	Light brown
Consistency:	Liquid
Type of film:	Oil/wax
Density:	23 – 26 mPas
Dry content:	50 – 60%
Volatiles solvents:	40 – 50%
Film thickness:	50 – 60µm
Application temperature:	<5° C
Removal with:	Clairsolrens, Clearrens or LHG Rensevæske
Drying time:	24 hours
Storing temperature:	5 – 25° C

For further information we recommend the safety data sheet or instruction on package.