

SUVO Bronze Belægning

Wax/oil/bitumen-based anti-corrosion product

Bronze-pigmented, light, thixotropic, wax/oil/bitumen-based anti-corrosion product. SUVO Bronze Belægning leaves a durable, leather-like, and flexible surface.

Range of application:

Used on underbodies, wheel arches, chassis frames, and areas exposed to heavy wear. A primer—such as SUVO 216, Rust Stop 80, or Rust Stop 150—must always be applied prior to the application of this product.

Package

01-1041 / 500 ml spray (12 pcs / pack)

01-922 / 25-lit can

01-921 / 60-lit drum

01-920 / 208-lit drum

Instructions for use:

Apply using a low-pressure or high-pressure system, or brush. Before application, the surface must be dry and free of loose flakes and dirt.

Technical data	
Color:	Bronze-pigmented
Consistency:	Thixotropic
Type of film:	Strong bitumen/wax
Density:	900 – 1100 mPas
Dry content:	60%
Volatiles solvents:	<40%
Film thickness:	200 – 250 µm
Application temperature:	20 – 40° C
Removal with:	Clairsolrens, Clearrens or LHG Rensevæske
Drying time:	24 hours at 23° C
Storing temperature:	5 – 25° C

For further information we recommend the safety data sheet or instruction on package.